

1- IDENTIFICATION

Product name: **FINAL TOUCH**
Description: Premium Tire and vinyl dressing
Product family: Non aqueous mixture
Supplier/Manufacturer: PARALL LTÉE
2970 Bergman, Laval, QC, H7L 3P4
Telephone: 450-687-6666 1 800-661-6660 fax: 450-687-7646
In case of emergency: CANUTEC (24 hours) (613) 996-6666 (collect)

2- HAZARDS IDENTIFICATION

Product classification:

Combustible liquid
Harmful by ingestion

Pictogram GHS:**Signal word:**

WARNING!

Individual protection:

Protection gloves and glasses are suggested.

3- COMPOSITION/INFORMATION ON INGREDIENTS

MIX

<u>Name</u>	<u>CAS Number</u>	<u>% weight</u>
Naphtha, hydrotreated heavy fraction	64742-48-9	60-100
Polydimethylsiloxane	not avail	15-40

4- FIRST AID MEASURES

Eye contact: Quickly rinse the eyes using a large amount of water for at least 15 minutes. See a doctor.

Skin contact: Remove contaminated clothing immediately using suitable gloves. Rinse skin with soap and water. Seek medical attention if irritation occurs.

Inhalation: Remove to a ventilated area and place in a semi-sitting position.

Ingestion: If swallowed, rinse mouth. Drink one or two glass of water. Do not induce vomiting and consult a doctor immediately.

5- FIRE-FIGHTING MEASURES

Flamability of the product: Combustible (flash point 59°C, tcc)

Extinguishing media: Use suitable extinguishing media suitable for the surrounding materials. Alcohol foam, carbon dioxide, dry powder, water pressure.

6- ACCIDENTAL RELEASE MEASURES

Personal protection: Respiratory protection with full face mask. Rubber gloves with long sleeve. Rubber boots. Tight tracksuits

Environmental precautions: Avoid dispersal from entering sewers, waterways or low areas.

Methods for cleaning: Small spill: Do not use tools that can create sparks. Mop up or absorb liquid with inert absorbent material. Contain residues in an airtight container. Refer to section 13 for waste disposal. Complete cleaning, rinsing with water.
Large spill: Ventilate the premises. Do not use tools that can create sparks. Absorb with inert absorbent material. Contain residues in an airtight container. Refer to section 13 for waste disposal. Complete cleaning, rinsing with water.

7- HANDLING AND STORAGE

Handling: Handle away from heat and ignition sources and incompatible materials. Wear waterproof gloves and safety glasses. Avoid repeated or prolonged skin contact. Avoid wearing lenses. May cause severe burns if swallowed.

Incompatibility with: Strong oxidizing agents: perchlorates, chromium trioxide, peroxides, sodium bichromate, trinitromethane, acids, ethylene oxide, isocyanates, etc. At high temperatures, it can react with oxygen from the air.

Storage: In a cool, well ventilated. Between 5 and 35 ° C.

8- EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures: Eyewash and emergency showers near the working place.

<u>Name</u>	<u>TLV (ACGIH)</u>
Naphtha, hydrotreated heavy fraction	300 ppm
Polydimethylsiloxane	not available

ACGIH : American Conference of Governmental Industrial Hygienists (2015)

TLV : Threshold limit value

TWA : Time-weighted average

STEL : Short-term exposure limit

**Consult local officials to know the exposure values considered acceptable.*

Personal protection

Respiratory: None generally required if ventilation is normal and proper.

Eye: Visor or safety goggles. Do not wear contact lenses when handling the product.

Hands: Rubber or neoprene gloves

Clothing: Use rubber apron or other protection depending on the nature of the job.

General: Do not wear contact lenses when handling the product.

9- PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Blue liquid	
Odour:	Fruity	
Odor threshold:	not available	
pH:	not applicable	
Freezing point / melting point:	not available	
Boiling point:	178-206°C	
Flash point:	59°C (Closed cup)	
Evaporating rate:	0.08	(ether=1)
Flammability:	Combustible	
Flammable limits	lower 1.2%v in air	upper 9.3%v in air
Vapor pressure:	0.6 (mm Hg)	
Vapor density:	5.6 (air=1)	
Specific gravity:	0.780	(water=1)
Solubility in water:	Not soluble	
N-octanol / water partition coefficient:	not available	
Auto ignition temperature:	349°C	
Decomposition temperature:	not available	
Viscosity:	not available	

10- STABILITY AND REACTIVITY

Chemical stability:	The product is stable under normal conditions. The container will tend to deform slightly. Store in a cool place.
Hazardous reactions:	Refer to Section 7 incompatible materials
Decomposition products:	When heated to a high temperature, the product may emit fumes of carbon monoxide, carbon dioxide, aldehydes and carboxylic acids.
Incompatibility with:	Refer to Section 7 incompatible materials

11- TOXICOLOGICAL INFORMATION

Datas: There are no data for the product, only for the ingredients

Name	<u>DL₅₀(rat, oral)</u>	<u>CL₅₀(rat, 4h)</u>
Naphtha, hydrotreated heavy fraction	>6000mg/kg	not av
Polydimethylsiloxane	not av	not av

Chronic health effects

Carcinogenic effects:	No data
Teratogenic effects:	No data
Reproductive effects:	No data
Synergistic product:	No data

12- ECOLOGICAL INFORMATION

Aquatic ecotoxicity:	No data
Earth ecotoxicity	No data
Biodegradability:	No data
Other adverse effects:	No data

13- DISPOSAL CONSIDERATIONS

Waste disposal: Disposal of all waste must be done according to local, provincial and federal regulations. Empty dry packaging can be recycled.

14- TRANSPORT INFORMATION

TGD classification: Not regulated
Additional information: TMD, exemption 1.33

15- REGULATORY INFORMATION

WHMIS 1998 (Canada): B3 Combustible liquid
 D2B Material causing other health effects. Irritating Skin / eye / respiratory

16- OTHER INFORMATION

Date of issue: 2017-09-11

Written by: Parall Ltée

References:

1. Manufacturer Datasheet
2. CNESST, Toxicological Directory, Products
3. Hazardous Products Regulations (SOR/2015-17)

Notice to reader

The best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards as described herein, we cannot guarantee that these are the only hazards that exist.

End of sheet